

# MAXIMA GA 5W-30

Fully Synthetic Motor Oil

## Description

Maxima GA 5W-30 is a fully synthetic engine oil developed for diesel and gasoline engines with particulate filter. It is recommended in particular for use in Opel, BMW and Mercedes-Benz vehicles which require the use of engine oils produced with low-ash technology. It has official GM Dexos2™ approval.

## Applications

Recommended for high performance gasoline and diesel passenger cars and light commercial vehicles. It is particularly well suited for Opel cars where Dexos2™ performance level is a requirement.

## Benefits

- The low ash, phosphorus and sulphur contents extend the life of exhaust systems, and protects the environment.
- It keeps the engine clean, decreases friction, and extends the life of the engine.
- It provides excellent wear control, in particular during starts.
- It provides fuel savings up to 3%.

## Performance

GM Dexos2™, API SN, ACEA A3/B4/C3, VW 502.00/505.00/505.01, MB 229.51, MB 229.52

## Typical Specifications\*

SAE Viscosity Grade		5W-30
Density, @ 15 °C, kg/m <sup>3</sup>	ASTM D 4052	0,848
Flash Point, COC, °C	ASTM D 92	228
Viscosity, 40 °C, mm <sup>2</sup> /s	ASTM D 445	60,36
Viscosity, 100 °C, mm <sup>2</sup> /s		11,2
Viscosity Index	ASTM D 2270	181
Pour Point, °C	ASTM D 97	-33

\* Values shown may differ between productions.

